

STRIP
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: June

With process factor valid for finished cold rolled and hardened and tempered strip products

Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

| GRADE | | | ALLOY & ENERGY SURCHARGE PER KG | | | | | | | | | | | |
|--|------------|--------|---------------------------------|--------|-------|------|-------|-------|-------|-------|-------|---------|---------|-------|
| Alleima | W.nr | ASTM | SS | SEK | EUR | GBP | USD | JPY | CAD | CNY | CHF | Lbs USD | Lbs CAD | BRL |
| Alloyed non-stainless steels and carbon steels | | | | | | | | | | | | | | |
| 20C | 1.1274 | 1095 | 1870 | 5,47 | 0,50 | 0,43 | 0,57 | 81 | 0,78 | 4,11 | 0,47 | 0,26 | 0,36 | 3,23 |
| 20C2 | | | 2258 | 5,82 | 0,53 | 0,45 | 0,60 | 86 | 0,83 | 4,37 | 0,50 | 0,27 | 0,38 | 3,43 |
| 10C16Mo3V1 | | | | 16,05 | 1,47 | 1,25 | 1,66 | 239 | 2,30 | 12,06 | 1,37 | 0,75 | 1,04 | 9,48 |
| Sanprint XP | | | | 15,51 | 1,42 | 1,21 | 1,60 | 231 | 2,22 | 11,65 | 1,32 | 0,73 | 1,01 | 9,16 |
| **** | | | | | | | | | | | | | | |
| Martensitic stainless chromium steels | | | | | | | | | | | | | | |
| 6C27 | 1.4007 | 420 | 2234 | 9,31 | 0,85 | 0,72 | 0,96 | 138 | 1,34 | 7,00 | 0,80 | 0,44 | 0,61 | 5,50 |
| 7C27Mo2 | | | | 15,24 | 1,39 | 1,18 | 1,58 | 227 | 2,18 | 11,45 | 1,30 | 0,71 | 0,99 | 9,00 |
| Hiflex | | | | 15,24 | 1,39 | 1,18 | 1,58 | 227 | 2,18 | 11,45 | 1,30 | 0,71 | 0,99 | 9,00 |
| Freeflex | | | | 16,06 | 1,47 | 1,25 | 1,66 | 239 | 2,30 | 12,06 | 1,37 | 0,75 | 1,04 | 9,48 |
| 10C28MO2 | | | | 15,38 | 1,40 | 1,20 | 1,59 | 229 | 2,21 | 11,56 | 1,31 | 0,72 | 1,00 | 9,08 |
| 12C27M | | | | 9,54 | 0,87 | 0,74 | 0,99 | 142 | 1,37 | 7,17 | 0,82 | 0,45 | 0,62 | 5,64 |
| 12C27 | | | | 9,27 | 0,85 | 0,72 | 0,96 | 138 | 1,33 | 6,97 | 0,79 | 0,43 | 0,60 | 5,48 |
| 14C28N | | | | 9,40 | 0,86 | 0,73 | 0,97 | 140 | 1,35 | 7,06 | 0,80 | 0,44 | 0,61 | 5,55 |
| 13C26 | | | 14141 | 9,10 | 0,83 | 0,71 | 0,94 | 135 | 1,30 | 6,84 | 0,78 | 0,43 | 0,59 | 5,37 |
| Damax | | | | 12,25 | 1,12 | 0,95 | 1,27 | 182 | 1,76 | 9,21 | 1,05 | 0,57 | 0,80 | 7,24 |
| 19C27 | | | | 9,27 | 0,85 | 0,72 | 0,96 | 138 | 1,33 | 6,97 | 0,79 | 0,43 | 0,60 | 5,48 |
| **** | | | | | | | | | | | | | | |
| Austenitic stainless steels | | | | | | | | | | | | | | |
| 12R11 | 1.4310 | 301 | 2331 | 21,73 | 1,98 | 1,69 | 2,25 | 323 | 3,12 | 16,33 | 1,86 | 1,02 | 1,41 | 12,83 |
| 11R51 | 1.4310 | 301 | 2231 | 25,71 | 2,35 | 2,00 | 2,66 | 382 | 3,69 | 19,32 | 2,20 | 1,21 | 1,67 | 15,18 |
| 13RM19 | EN 1.4369 | | | 22,00 | 2,01 | 1,71 | 2,28 | 327 | 3,15 | 16,53 | 1,88 | 1,03 | 1,43 | 12,99 |
| 3X22R60HV | 1.4441 | 316LVM | | 49,39 | 4,51 | 3,84 | 5,11 | 734 | 7,08 | 37,10 | 4,22 | 2,32 | 3,21 | 29,16 |
| 2RK65HV | | | | 73,24 | 6,69 | 5,69 | 7,57 | 1 089 | 10,50 | 55,02 | 6,26 | 3,44 | 4,76 | 43,25 |
| 3X8R65 | | | | 38,72 | 3,53 | 3,01 | 4,00 | 575 | 5,55 | 29,09 | 3,31 | 1,82 | 2,52 | 22,86 |
| 3R60F1 | | | | 47,75 | 4,36 | 3,71 | 4,94 | 710 | 6,85 | 35,88 | 4,08 | 2,24 | 3,11 | 28,20 |
| **** | | | | | | | | | | | | | | |
| Precipitation hardenable steels | | | | | | | | | | | | | | |
| 9RU10 | 1.4568 | 631 | 2388 | 22,01 | 2,01 | 1,71 | 2,28 | 327 | 3,16 | 16,54 | 1,88 | 1,03 | 1,43 | 13,00 |
| NANOFLEX | | | | 48,85 | 4,46 | 3,80 | 5,05 | 726 | 7,00 | 36,70 | 4,17 | 2,29 | 3,18 | 28,85 |
| 1RK95 | | | | 21,89 | 2,00 | 1,70 | 2,26 | 325 | 3,14 | 16,45 | 1,87 | 1,03 | 1,42 | 12,93 |
| **** | | | | | | | | | | | | | | |
| Duplex stainless steels (austenitic-ferritic) | | | | | | | | | | | | | | |
| SAF2205 | EN 1.4462 | | 2377 | 39,48 | 3,60 | 3,07 | 4,08 | 587 | 5,66 | 29,66 | 3,37 | 1,85 | 2,57 | 23,32 |
| SAF2507 | EN 1.4410 | | 2328 | 46,06 | 4,20 | 3,58 | 4,76 | 685 | 6,60 | 34,61 | 3,93 | 2,16 | 3,00 | 27,20 |
| SAF3207HD | | | | 45,42 | 4,15 | 3,53 | 4,70 | 675 | 6,51 | 34,13 | 3,88 | 2,13 | 2,95 | 26,82 |
| **** | | | | | | | | | | | | | | |
| Ferritic stainless chromium steel | | | | | | | | | | | | | | |
| 1C429 | | | | 12,13 | 1,11 | 0,94 | 1,25 | 180 | 1,74 | 9,11 | 1,04 | 0,57 | 0,79 | 7,16 |
| 1C44Mo20 | | | | 17,67 | 1,61 | 1,37 | 1,83 | 263 | 2,53 | 13,27 | 1,51 | 0,83 | 1,15 | 10,43 |
| 0XC34 | | | | 10,27 | 0,94 | 0,80 | 1,06 | 153 | 1,47 | 7,72 | 0,88 | 0,48 | 0,67 | 6,07 |
| 1C34 | | | | 10,21 | 0,93 | 0,79 | 1,06 | 152 | 1,46 | 7,67 | 0,87 | 0,48 | 0,66 | 6,03 |
| **** | | | | | | | | | | | | | | |
| Nickel-base alloy | | | | | | | | | | | | | | |
| SANICRO75X2 | UNS N07750 | | | 123,04 | 11,23 | 9,56 | 12,72 | 1 829 | 17,64 | 92,44 | 10,51 | 5,77 | 8,00 | 72,66 |
| SAN62TINb | | | | 107,34 | 9,80 | 8,34 | 11,10 | 1 596 | 15,39 | 80,64 | 9,17 | 5,04 | 6,98 | 63,38 |
| **** | | | | | | | | | | | | | | |
| Energy surcharge per kg included in total surcharge | | | | 2,30 | 0,21 | 0,18 | 0,24 | 34 | 0,33 | 1,73 | 0,20 | 0,11 | 0,15 | 1,36 |